

SAFETY DATA SHEET**swift®lock 2U258-2N**

Version 1.3

Revision Date 10/04/2017

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : swift®lock 2U258-2N
Product code : 100000001129

Manufacturer or supplier's details

Company : H.B. Fuller Company
Address : 1200 Willow Lake Boulevard
Vadnais Heights, MN 55110
Telephone : 1-888-423-8553

Medical Emergency Phone Number (24 Hours): 1-888-853-1758

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

Recommended use of the chemical and restrictions on use

Recommended use : Hot melt moisture cure adhesive
Restrictions on use : For industrial use only.

SECTION 2. HAZARDS IDENTIFICATION**Emergency Overview**

| | |
|------------|----------------|
| Appearance | Solid form |
| Color | off-white |
| Odor | characteristic |

GHS Classification

Skin irritation : Category 2
Eye irritation : Category 2A
Respiratory sensitization : Category 1
Skin sensitization : Category 1
Carcinogenicity : Category 2
Specific target organ systemic toxicity - repeated exposure : Category 2

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements:

H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H351

SAFETY DATA SHEET
swift®lock 2U258-2N

Version 1.3

Revision Date 10/04/2017

Suspected of causing cancer. H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements:

Prevention: P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray. P264 Wash skin thoroughly after handling. P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P285 In case of inadequate ventilation wear respiratory protection.

Response: P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P304 + P341 IF INHALED: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308 + P313 IF exposed or concerned: Get medical advice/ attention. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P337 + P313 If eye irritation persists: Get medical advice/ attention. P362 Take off contaminated clothing and wash before reuse.

Storage: P405 Store locked up.

Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.

Potential Health Effects

Inhalation : Vapors/fumes may be irritating at application temperatures.

Skin : Contact with hot product will cause thermal burns.

Aggravated Medical Condition : None known.

Carcinogenicity:
IARC

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous ingredients

| Chemical name | CAS-No. | Concentration [%] |
|-------------------------------------|--------------|-------------------|
| Proprietary isocyanate prepolymer | Not Assigned | 90 - 100 |
| 4,4'-methylenediphenyl diisocyanate | 101-68-8 | 1 - 5 |

SECTION 4. FIRST AID MEASURES

General advice : Show this material safety data sheet to the doctor in attendance.

SAFETY DATA SHEET**swift®lock 2U258-2N**

Version 1.3

Revision Date 10/04/2017

- If inhaled : Move to fresh air.
If symptoms persist, call a physician.
- In case of skin contact : Wash off with soap and water.
Cool melted product on skin with plenty of water. Do not
remove solidified product.
- In case of eye contact : In the case of contact with eyes, rinse immediately with plenty
of water and seek medical advice.
- If swallowed : Do not induce vomiting. Seek medical attention if symptoms
develop. Provide medical care provider with this SDS.
- Notes to physician : Use mineral oil to soften and loosen product for removal.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or
carbon dioxide.
- Unsuitable extinguishing media : Do NOT use water jet.
- Specific hazards during fire fighting : Burning produces irritant fumes.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if
necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Refer to protective measures listed in sections 7 and 8.
- Methods and materials for containment and cleaning up : Allow to solidify.
Scrape up.
Shovel into suitable container for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : No special precautions are needed in handling this material.
Avoid breathing vapors/fumes of heated product. Prevent
contact with molten product.
- Conditions for safe storage : Keep in a dry, cool place.
- Materials to avoid : No special restrictions on storage with other products.

SAFETY DATA SHEET
swift®lock 2U258-2N

Version 1.3

Revision Date 10/04/2017

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Ingredients with workplace control parameters

| Ingredients | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|-------------------------------------|----------|----------------------------------|---|-----------|
| 4,4'-methylenediphenyl diisocyanate | 101-68-8 | TWA | 0.005 ppm | ACGIH |
| | | C | 0.02 ppm 0.2 mg/m ³ | OSHA Z-1 |
| | | C | 0.02 ppm 0.2 mg/m ³ | OSHA P0 |
| | | C | 0.02 ppm 0.2 mg/m ³ | OSHA Z-1 |
| | | C | 0.02 ppm 0.2 mg/m ³ | OSHA P0 |
| | | TWA | 0.005 ppm 0.05 mg/m ³ | NIOSH REL |
| | | C | 0.02 ppm 0.2 mg/m ³ | NIOSH REL |
| | | PEL | 0.005 ppm 0.051 mg/m ³ | CAL PEL |

Engineering measures : At the application temperature, use of local exhaust over the premelting reservoir is encouraged.

Personal protective equipment

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.

Filter type : Combined particulates and organic vapor type

Hand protection

Material : Nitrile rubber

Remarks : When handling hot material, use heat resistant gloves.

Eye protection : Safety glasses

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Solid form
 Color : off-white
 Odor : characteristic
 Odor Threshold : No data available
 Boiling point/boiling range : not determined

SAFETY DATA SHEET**swift®lock 2U258-2N**

Version 1.3

Revision Date 10/04/2017

| | |
|--|---|
| Evaporation rate | : not determined |
| Flammability (solid, gas) | : Not classified as a flammability hazard |
| Upper explosion limit | : Upper flammability limit not determined |
| Lower explosion limit | : Lower flammability limit not determined |
| Relative vapor density | : not determined |
| Density | : 8.4 - 10.0 lb/gal |
| Solubility(ies) | |
| Water solubility | : insoluble |
| Partition coefficient: n- octanol/water | : No data available |
| Autoignition temperature | : not determined |
| Thermal decomposition | : Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). |
| Viscosity | |
| Viscosity, kinematic | : Not applicable |
| Solid Content, % by weight: | : 100 |

SECTION 10. STABILITY AND REACTIVITY

| | |
|---------------------------------------|--|
| Reactivity | : Container can be pressurized by carbon dioxide due to reaction with humid air and/or water. |
| Chemical stability | : The product is chemically stable. |
| Possibility of hazardous reactions | : Hazardous polymerization does not occur. |
| Hazardous decomposition products | : In case of incomplete combustion an increased formation of oxides of nitrogen (NOx) is to be expected. Thermal decomposition can lead to release of irritating gases and vapors. Humid air and/or water will produce carbon dioxide which will pressurize the container. Stable under normal conditions. |

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity****Product:**

| | |
|---------------------------|--|
| Acute inhalation toxicity | : Acute toxicity estimate : 39.47 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation method |
|---------------------------|--|

SAFETY DATA SHEET**swift®lock 2U258-2N**

Version 1.3

Revision Date 10/04/2017

Ingredients:**101-68-8:**

Acute inhalation toxicity : LC50 : 1.5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT-single exposure

No data available

STOT-repeated exposure

No data available

Aspiration toxicityNo data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity**

No data available

Persistence and degradability

No data available

Bioaccumulative potential**Mobility in soil**

No data available

Other adverse effects

SAFETY DATA SHEET**swift®lock 2U258-2N**

Version 1.3

Revision Date 10/04/2017

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Dispose of in an approved landfill. Consult your state, local or provincial authorities and your local waste vendor for more restrictive requirements. The hazard and precautionary statements displayed on the label also apply to any residues left in the container.

SECTION 14. TRANSPORT INFORMATION**Special precautions for user**

Not applicable

Domestic regulation**49 CFR**

Not regulated as a dangerous good

International Regulations**UNRTDG**

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : Skin corrosion or irritation
Serious eye damage or eye irritation
Respiratory or skin sensitization
Carcinogenicity
Specific target organ toxicity (single or repeated exposure)

SARA 302 : This material does not contain any components with a section 302 EHS TPQ.

SAFETY DATA SHEET**swift®lock 2U258-2N**

Version 1.3

Revision Date 10/04/2017

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

| | |
|-------------------------------------|----------|
| 4,4'-methylenediphenyl diisocyanate | 101-68-8 |
|-------------------------------------|----------|

Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

| | |
|-------------------------------------|----------|
| 4,4'-methylenediphenyl diisocyanate | 101-68-8 |
|-------------------------------------|----------|

US State Regulations

California Prop 65 This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

The ingredients of this product are reported in the following inventories:

| | |
|--------------|--|
| TSCA | On TSCA Inventory |
| DSL | This product contains one or several components that are not on the Canadian DSL nor NDSL. |
| REACH | Not in compliance with the inventory |
| AICS | Not in compliance with the inventory |
| NZIoC | Not in compliance with the inventory |
| ENCS | Not in compliance with the inventory |
| KECI | Not in compliance with the inventory |
| PICCS | Not in compliance with the inventory |
| IECSC | Not in compliance with the inventory |
| TWINV | Not in compliance with the inventory |

Inventories Legend TSCA (USA), DSL (Canada), REACH(Europe), AICS (Australia), NZIoC (New Zealand), ENCS (Japan), KECI (Korea), PICCS (Philippines), IECSC (China), TWINV (Taiwan)


SECTION 16. OTHER INFORMATION

Prepared by: Global Regulatory Department - phone: 1-651-236-5842 - email: msds.request@hbfuller.com

SAFETY DATA SHEET
swift®lock 2U258-2N

Version 1.3

Revision Date 10/04/2017

Further information
NFPA:

HMIS III:

| | |
|------------------------|-----------|
| HEALTH | 2* |
| FLAMMABILITY | 1 |
| PHYSICAL HAZARD | 0 |

0 = not significant, 1 = Slight,
 2 = Moderate, 3 = High
 4 = Extreme, * = Chronic

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to the H.B. Fuller Company from its suppliers, and because the H.B. Fuller Company has no control over the conditions of handling and use, the H.B. Fuller Company makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and the H.B. Fuller Company assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Company products to comply with all applicable federal, state and local laws and regulations.